

LSV SERIES

**250 mm Submersible Pumpset
50 Hz**



QUALITY • INNOVATION • SUSTAINABILITY

250 mm

10" Borewell Submersible Pumpsets



10" Submersible pumpsets for 250 mm. DIA. Borewell. (245 mm. Max. Diameter) MIXED FLOW

LSP-150A Outlet size 150mm. (6") n = 2880 rpm

Pump Type	Stage	K.W.	H.P.	Discharge in L.P.M.						
				0	1000	1160	1440	1800	2130	2450
				Head in Metres						
LSP 150A	1	11.0	15.0	34	30	29	27	24	21	18
LSP 150A	2	22.0	30.0	67	60	58	54	48	42	36
LSP 150A	3	33.0	45.0	101	90	87	81	72	63	54
LSP 150A	4	45.0	60.0	134	120	116	108	96	84	72
LSP 150A	5	55.0	75.0	168	150	145	135	120	105	90
LSP 150A	6	66.0	90.0	201	180	174	162	144	126	108
LSP 150A	7	79.0	105.0	235	210	203	189	168	147	126
LSP 150A	8	90.0	120.0	268	240	232	216	192	168	144

LSP-200A Outlet size 150mm. (6") n = 2880 rpm

Pump Type	Stage	K.W.	H.P.	Discharge in L.P.M.					
				0	1300	2000	2500	3000	3400
				Head in Metres					
LSP 200A	1	15.0	20.0	34	28	25	22	19	14
LSP 200A	2	30.0	40.0	68	56	50	44	38	28
LSP 200A	3	45.0	60.0	102	84	75	66	57	42
LSP 200A	4	60.0	80.0	136	112	100	88	76	56
LSP 200A	5	75.0	100.0	170	140	125	110	95	70
LSP 200A	6	90.0	120.0	204	168	150	132	114	84

LSP-250A Outlet size 150mm. (6") n = 2880 rpm

Pump Type	Stage	K.W.	H.P.	Discharge in L.P.M.						
				0	1600	2180	2550	2900	3200	4000
				Head in Metres						
LSP 250A	1	18.5	25.0	35	30	27	25	23	21	16
LSP 250A	2	37.0	50.0	70	60	54	50	46	42	32
LSP 250A	3	55.0	75.0	105	90	81	75	69	63	48
LSP 250A	4	75.0	100.0	140	120	108	100	92	84	64

LSP-300A Outlet size 150mm. (6") n = 2880 rpm

Pump Type	Stage	K.W.	H.P.	Discharge in L.P.M.						
				0	2600	3200	3700	4150	4530	4820
				Head in Metres						
LSP 300A	1	22.0	30.0	34	28	26	24	22	20	18
LSP 300A	2	45.0	60.0	68	56	52	48	44	40	36
LSP 300A	3	66.0	90.0	102	84	78	72	66	60	54
LSP 300A	4	90.0	120.0	136	112	104	96	88	80	72

Borewell Submersible pumpsets MIXED FLOW

LSP-350A Outlet size 250mm. (10") n = 2880 rpm

Pump Type	Stage	K.W.	H.P.	Discharge in L.P.M.						
				0	2300	3500	4600	5100	5300	5400
				Head in Metres						
LSP 350A	1	26.0	35.0	41	35	30	25	22	18	15
LSP 350A	2	52.0	70.0	81	70	60	50	44	35	30
LSP 350A	3	75.0	100.0	122	105	90	75	66	53	45
LSP 350A	4	110.0	150.0	162	140	120	100	88	70	60
LSP 350A	5	130.0	175.0	203	175	150	125	110	88	75
LSP 350A	6	150.0	200.0	243	210	180	150	132	105	90
LSP 350A	7	184.0	250.0	284	245	210	175	154	123	105

LSP-500A Outlet size 250mm. (10") n = 2880 rpm

Pump Type	Stage	K.W.	H.P.	Discharge in L.P.M.						
				0	3100	4000	5600	7100	7700	8100
				Head in Metres						
LSP 500A	1	37.0	50.0	41	33	30	25	20	18	15
LSP 500A	2	75.0	100.0	82	65	60	50	40	35	30
LSP 500A	3	110.0	150.0	123	98	90	75	60	53	45
LSP 500A	4	150.0	200.0	164	130	120	100	80	70	60
LSP 500A	5	184.0	250.0	205	163	150	125	100	88	75

Note :

- LSP models upto 80 HP will be supplied with 8" motor. (10" motor will be available on request with extra cost).
- LSP models above 80 HP will be supplied with 10" motor.
- Please select pumps in the range of discharge shown in bold figure.
- All V8 motors are ISI as per ISI : 9283. [12.5 HP to 60 HP, **Except 17.5 HP**].

LUBI INDUSTRIES LLP

Near Kalyan Mills, Naroda Road, Ahmedabad-380 025, INDIA.

Phone : +91 - 79 - 61700100, Fax No. :+91 - 79 - 61700399.

Sales Enquiries: mktsales@lubipumps.com

www.lubipumps.com

Product Improvement is a continuous process at 'LUBI'. The data given in this publication is therefore subject to revision.



ISO 9001



ISO 14001

Customer Care Number : 09824200800